

# AD 710

Doosan  
Mecc Alte  
D+ &



ISO8528

GC, ) &

SZUTEST

GC - \$\$\$



2000/14/EC

&\$\$\$#( #

z) \$ z' z' D:

	"	kw	"	kw	Amp
400/230	710,00	568,00	640,00	512,00	923,80

fP GDE

GC, ) &

,) & z

fDF DE

%\$!

% %&

GC" \$(\*"

z&(

GC

## Standard Specifications

z

fl

E

z

z

## ALTERNATOR

D; A Z' 5J F

## TRANSFER SWITCH

# AD 710

Doosan  
Mecc Alte  
D+' &'

Manufacturer	Doosan		
Model	DP180LB		
		612,00 kw [820,00HP]	
	L	18,273	
	"	128 x 142	
		15,0:1	
	fl # 7	"# "	1500
	fl 7	L	34,00
		L	112,20
AbsorbedAirDischargeReSourceKey.Text	' # "	36,00	
	' # "	700,00	
	' # "	118,00	
	° C	587,00	
		24 V d.c.	
	Load	%\$i	+) i
	# "	) \$i	
		136,40	103,80 71,20

	Mecc Alte		
	ECO40 2L/4		
	Hz	50	
	"	680,00	
7cg'		0,80	
		3	
	fl 7	400/230	
	A	981,50	

		fl 7		fl 7	
	"	"	"	"	L
AD 710	4000,00	3359,00	1550,00	2056,00	850,00
		fl 7		fl 7	
	"	"	"	"	L
MS 80	4940	4810	1606	2615	850



# AD 710

Doosan  
Mecc Alte  
D+' &''



f@#@Bl  
f@#@Bl

"z" "z"

f@#@Bl

971

#

#

#

#



#

6G'9B'\*\$-)\$

6G'9B'\*\$\$\$!\*!&

6G'9B'\*\$\$\$!\*!(

f&%) +L

f&)(, L

f&% \$L



'GA 8'

'!&+""

%, !&\*(

&(\$)

ž

ž

ž

# AD 710

Doosan  
Mecc Alte  
D+ &''



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 in front and back side special large access doors for easy maintenance
- 9 Base frame -fuel tank.
- 10 Lifting points similar to ISO container , located on each top corner of the canopy
- 11 the canopy provides easy access to radiator cap.
- 12 sound proofing materials
- 13 Plastic air intake pockets.

	"	1606
fl "L	"	4810
fl "L	"	2615
	L	850