



INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

Certificate

ISO 14001-2004

TS ISO 8528

TS ISO 9001-2008

CE

SZUTEST

2000/14/EC

General Characteristics

Model Name	AC 3750
Frequency (Hz)	50
Fuel Type	Diesel
Engine Made and Model	CUMMINS - QSK95-G4
Alternator Made and Model	Stamford - HVSI804X WDG 83 (11kV)
Control Panel Model	DSE 7320

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.


Canopy

CONTAINER

3 Phase, 50 Hz, PF 0.8

VOLTAGE	STANDBY RATING (ESP)		PRIME RATING (PRP)		Standby Amper
	kVA	kW	kVA	kW	
400/231	3750	3000.00	3320	2656.00	5412.82

STANDBY RATING (ESP) : Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

PRIME RATING (PRP) : Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation.

ENGINE SPECIFICATIONS

Engine		CUMMINS
Engine Model		QSK95-G4
NO. OF CYLINDERS AND BUILD		16 cylinders - V type
BORE AND STROKE	mm	190 X 210
TOTAL DISPLACEMENT	L	95

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



Aspiration		Turbocharged and Low Temperature Aftercooled	
COMPRESSION RATIO		15.5:1	
RATED SPEED (RPM)	d/dk	1500	
OIL CAPACITY	L	647	
Standby Power (kW/HP)		3245/4351	
Prime Power		2883/3866	
Block Heater QTY			
		2	
Block Heater Power (Watt)			
		3000	
Fuel Type			
		Diesel	
Injection Type and System			
		Direct	
Type of Fuel Pump			



	Cummins MCRS		
Governor System			
		Electronic	
Operating Voltage (Vdc)			
		24 Vdc	
Battery and Capacity (Qty/Ah)			
		6x143	
Charge Alternator (A)			
		140	
Cooling Method			
		Water Cooled	
Coolant Capacity (engine only / with radiator) (lt)			
		323/	
Air Filter			
		Dry Type	
Fuel Cons. Prime With %100 Load (lt/hr)			



	645		
Fuel Cons. Prime With %75 Load (lt/hr)			
		483	
Fuel Cons. Prime With %50 Load (lt/hr)			
		333	


ALTERNATOR SPECIFICATIONS

Manufacturer		Stamford
Alternator Made and Model		HVSI804X WDG 83 (11kV)
Frequency (Hz)	Hz	50
Power (kVA)	kVA	3724
DESIGN		4 Pole, Brushless
VOLTAGE	V	11000
Phase		3
A.V.R.		MA330



Voltage Regulation	(+/-)	0,5
Insulation System		F Class
Protection		IP23
Rated Power Factor		0.8
WEIGHT COMP. GENERATOR (Kg)		-
COOLING AIR (m³/min)	m³	225

SIZE and WEIGHT

Open Type	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
	2000 (approx.)	6050	2597	3443	6000
CANOPY	DRY WEIGHT (kg.) (kg.)	LENGTH (mm.)	WIDTH (mm.)	HEIGHT (mm.)	TANK CAPACITY (lt.) (Lt.)
CONTAINER		12192	2044	2592	0

STANDART SPECIFICATIONS

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



Water cooled diesel engine
Remote Radiator with electricfan
Protective grille for rotating and hot parts
Electric starter and charge alternator
Starting battery (with lead acid) including rack and cables
Engine coolant heater
Steel base frame and anti-vibration isolators
Spare external fuel tank (open set)
Flexible fuel connection hoses
Single bearing, class F alternator
Industrial exhaust silencer and steel bellows supplied separately
Static battery charger
Manual for application and installation
Generators Sets' voltage and frequency regulation comply with ISO 8528-5

OPTIONAL EQUIPMENTS

ENGINE

- Electronic governor control
- Fuel-Water Separator Filter
- Low water level alarm
- Oil heater

ALTERNATOR

- Anti-Condensation Heater
- Over sized alternator
- PMG excitation + AVR
- Single Phase (4 lead)
- Main line circuit breaker

CONTROL SYSTEM

- Automatic synchronising and power control system (multi gen-set Parallel)
- Paralel system with mains.
- Transition synchronization with mains
- Remote annunciator panel
- Remote relay output
- Alarm output relays
- Remote communication with modem
- Earth fault, single set
- Charge Ammeter

TRANSFER SWITCH

Производитель сохраняет за собой право без предварительного уведомления делать изменения в моделях, технических характеристиках, цветах, оборудовании, аксессуарах и чертежах.



- Three Pole Contactor
- Four Pole Contactor
- Three or four pole contactor
- Motorlu Şalter
- Three or four pole motor operated circuit breaker

OTHER ACCESSORIES

- Main Fuel Tank
- Automatic or manual fuel filling system
- Manual oil drain pump
- Electrical oil drain pump
- Low and high fuel level alarm
- Residential silencer
- Enclosure: weater protective or sound attenuated
- Duct adapter (on radiator)
- Inlet and outlet motorised louvers
- Inlet and outlet acoustic baffles
- Trailer
- Tool kit for maintenance
- 1500/3000 hours maintenance kit
- Double wall chassis
- Supplied with oil and coolant - 30 °C
- Battery isolating switch
- Battery heater
- Automatic transfer switch